



# PRO SERIES

# MULTIFEEDER 6000



## FEATURE

Standard



## USED BY

- Banks / Credit Institutions
- Insurance Companies
- Casinos
- Clubs / Associations
- Government Offices
- Petroleum Companies
- Service Bureaus

## IDEAL FOR

- High volume smart card encoding
- Credit cards and other financial cards\*
- ID cards
- Prepaid cards
- Selective load of 6 different type of cards in-line with other Pro Series systems

\* compatible with most 3rd party EMV personalization software solutions.

## IN LINE SOLUTIONS

- THERMAL 1000 / 2000
- COMBI 1000
- EMBOSSER 1000 / 2000
- INSERTER 3000
- LABEL DISPENSER 1500
- VISION 3000



## SMART CARD ENCODING

## FEED AND PROCESS UP TO 6 CARDS SIMULTANEOUSLY AND FAST

## SOFTWARE

(MULTICARD 2006)

Chip contact station on each hopper

Card thickness: 0,76 mm or 0,80 mm  
Card size: ISO standard CR-80





# PRO SERIES

# MULTIFEEDER 6000

## SPECIFICATIONS



## MULTIFEEDER 6000



**input hopper**  
**output hopper**

6 input hoppers, 200 cards each (0,76 mm)  
200 cards, with 40 card capacity reject hopper

**card format**  
**card thickness**  
**card materials**

CR80 - ISO standard  
0,76 mm to 0,80 mm / 30 to 32 mil  
ABS, PVC and composite

**chip contact station**  
**communication interface**  
**power supply**  
**power consumption**  
**operating environment**  
**relative humidity**

6 contact stations standard  
RS232 serial port power supply  
117 V / 60 Hz – 230 V / 50 Hz  
150 W, including chip option 250 W  
10°C to 35°C / 50°F to 95°F  
20% - 85% non condensing

**dimensions (WxDxH)**  
**weight**  
**floor stand**

860 x 480 x 350 mm / 33.8" x 18.9" x 13.8"  
99,6 Kg / 219.6 lbs  
Optional (required for in-line operation)

**operating systems**  
**software/firmware**

Windows 2000/XP  
Windows based application software. Self diagnostic; automatic repetition of faulty card; resettable and non-resettable counters, system state and help messages displayed on PC.

**in-line configuration**

The Pro Series units can operate in a stand alone or in-line configuration with 2 up to 5 equipments. The MULTIFEEDER 6000 can be connected to: THERMAL 1000/2000, COMBI 1000, EMBOSSER 1000/2000, INSERTER 3000, LABEL DISPENSER 1500, VISION 3000.

**FAST AND FLEXIBLE:** The MULTIFEEDER 6000 makes multi-card processing simple, offering you complete flexibility and practicality with its 6 input hoppers capable of holding 200 cards each.

**CONVENIENT AND VERSATILE:** The MULTIFEEDER 6000 can be optionally equipped with a chip encoding station for high speed smart card personalization.



All trademarks belong to their respective owners. MF6000\_ING REV. 03-11/05



CIM SpA  
Via O. Serra, 2 - Loc. Lippo - 40012 Calderara di Reno (BO) - ITALIA  
Tel. +39 051 6465 011 - Fax +39 051 6465 012  
www.cimitaly.it - info@cimitaly.it

CIM USA, Inc  
10813 NW 30th Street - Suite 108 - Miami, FL 33172  
Tel. 305-639-3040 - Fax 305-639-3060  
www.cim-usa.com - www.cimgsa.com - info-usa@cim-usa.com

